



SUNKOLL TILE LOBSTER

DESCRIPTION

- Sunkoll tile lobster is back tile primer

AREAS OF APPLICATION

- Apply (Brush / spray) Sunkoll tile lobster on the reserve side of the tile / wall and let it dry for 15-30 minutes.
- For highly porous stone , apply one coat of elastobar on the reserve side of tile / wall, let it dry for 6-8 hours .then apply Sunkoll tile lobster.
- Apply Sunkoll tile lobster on the plastered cementitious dry for 15-30 minutes. within 1-2 hours, apply 6 to 8 mm mortar (1:2 cement and sand



- mix) layer on the Sunkoll tiles lobster treated surface.
- Immediately fix the tile on the surface where mortar has been applied. Allow a curing period of 28 days under normal weather conditions for best result.

FEATURES

- Immediately after the primer is applied, the tile and wall adhesive give a longer grip.
- High open time & antisag properties
- Good adjustability time with high water retention even at elevated temperature
- It can be used with both grey and white cement
- Suitable for Ceramic & Vitrified tiles

BENEFITS

- Easy to use, no special tools required
- Economical solution for tile fixing
- Low VOC environmentally safe

STORAGE & SHELF LIFE

Store in a shaded area away from direct sunlight, between 5-45° C. protect from extreme temperatures. Shelf life of Sunkoll tile lobster is 48 months when stored as recommended.

Technical information

Usage/Application	Residential, Commercial
Brand	SUNKOLL
Packaging Type	Plastic Bottle
Physical State	Liquid
Shelf Life	48 Months
Packaging Size	500 g, 1 to 5 Kg
Tiles Size	Up To 4 m2
Coverage	3.5 to 4m2 (40 to 45 Feet2) per Kg