

SUNKOLL TILE EPOXY

Technical Data Sheet

SUNKOLL[®]
ABILITY ♦ STABILITY ♦ DURABILITY

नए भारत की नई ताकत

How To Use



Application Areas

- Wall Tiles & Floor Tiles
- Interiors & Exteriors
- Shower, Swimming Pool
- Heavily Traffic Area
- Hygienic Sterile
- Chemical Resistance Area
- Hydrotherapy Pools

Features

- Stain Free
- Easy to Install & Clean
- Water Cleanable
- Non Creaking
- Anti-bacterial & Anti-Fungal
- High Glossy
- Chemical & Temperature Resistance
- Easy Maintenance
- Hard & Durable Joints
- Waterproof & Acid Proof

Application Procedure :

- Mix 100 gram Hardener & 200 gram Resin. After that Mix 700 gram Filler Powder and Make a good paste, fill the joints properly and slightly rub with wetted sponge after 10 MM.

Packaging :

- SUNKOLL TILES EPOXY is supplied in 1 kg. | 5 kg. | 20 kg. pack.

Coverage :

- Depends on Joints Width & Depth

www.sunkoll.com

Water Proofing Chemicals | Adhesives | Grouts/Epoxy Grouts | Wall Putty

Technical Information

PROPERTIES	RESULT
Joint Width	2 to 10 mm
Gel Time	60 min.
Specific Gravity	1.75
Water Absorption	Nil

Application Areas :

- Stain Free
- Color-Fast
- Easy to Install & Clean
- Chemical & Temperature Resistant
- Non-Cracking or Powdering
- Water Cleanable when Fresh
- Available in Range of Attractive Color

Technical Properties

Compressive Strength	65 N/mm ²
Tensile Strength	65 N/mm ²
Bond Strength	65 N/mm ²
Port Life	40 to 45 Minute
Final Strength	72 Hours

**SUNKOLL
TILE EPOXY**

SUNKOLL[®]
ABILITY ♦ STABILITY ♦ DURABILITY

नए भारत की नई ताकत



SUNKOLL Green Building Index :

SUNKOLL Range of Products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, SUNKOLL procure the major raw material locally to safeguard environment.

SUNKOLL Quality & Safety Assurance

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.

Declaration :

All the above information and results are provided based on **SUNKOLL** internal quality test. Customer must check before using the product about performance and final expected results. **SUNKOLL** cannot be held responsible for any damage of whatsoever nature at site.

SUNKOLL INDUSTRIES LIMITED

Plot No. 62, Tarang Industrial Estate
Hadamtada Ta. Kotda Sangani N.H. 8-B
Rajkot(Gujarat) - 360 311

TECHNICAL SERVICES & CUSTOMER CARE : +91 70698 82251

TOLL FREE : 1800 890 2343

Email: sunkollindltd@gmail.com

www.sunkoll.com

Water Proofing Chemicals | Adhesives | Grouts/Epoxy Grouts | Wall Putty