

### Polymer modified Grout for Wall & Floor tiles Joints

#### How To Use



#### Usage

- Impermeable to Water
- Resistant to shrinking, flaking or cracking
- Non – fading over a period of time
- Easy to apply
- Non shrink
- Durable
- Good abrasion resistance

#### Application Area

- Wall Tiles
- Floor Tiles
- Interiors & Exteriors

#### Coverage :

- Depends on joints Width & Depth

#### Packaging :

- SUNKOLL TILE GROUT is supplied in 500 gm 1kg & 20Kg

### Application Procedure :

- 300 ml. clean water to be used in 1 kg .powder ,mix it Properly and apply with trowel. You can add 200ml. Sunkoll Bond Repair and SBR Acrylic to increase strength and durability.

### Technical Specification

PROPERTIES	RESULTS
Pot Life @ 30°C	120 min.
Open time	60 min.
Adjustment Time	15 -20 min.
Initial setting Time	2 Hr.
Final setting Time	24 Hr.
Shrinkage	<0.1%
Final Strength	28 Day

**SUNKOLL  
TILE GROUT**

**SUNKOLL<sup>®</sup>**  
**ABILITY ♦ STABILITY ♦ DURABILITY**

नए भारत की नई ताकत



### **SUNKOLL Green Building Index :**

SUNKOLL Range of Products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, SUNKOLL procure the major raw material locally to safeguard environment.

### **SUNKOLL Quality & Safety Assurance**

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.

### **Declaration :**

All the above information and results are provided based on **SUNKOLL** internal quality test. Customer must check before using the product about performance and final expected results. **SUNKOLL** cannot be held responsible for any damage of whatsoever nature at site.

## **SUNKOLL INDUSTRIES LIMITED**

Plot No. 62, Tarang Industrial Estate  
Hadamtda Ta. Kotda Sangani N.H. 8-B  
Rajkot(Gujarat) - 360 311

**TECHNICAL SERVICES & CUSTOMER CARE : +91 70698 82251**

**TOLL FREE : 1800 890 2343**

**Email: [sunkollindltd@gmail.com](mailto:sunkollindltd@gmail.com)**

**[www.sunkoll.com](http://www.sunkoll.com)**

Water Proofing Chemicals | Adhesives | Grouts/Epoxy Grouts | Wall Putty