

# SUNKOLL CRACK PACKR

## Technical Data Sheet



नए भारत की नई ताकत

SUNKOLL CRACK PACKR, is ready to use fiber glass reinforced crack filling compound for both interior and exterior surface. It ensures unmatched crack bridging ability for plaster cracks of up to 3 mm.

### How To Use



### Product Benefits of Sunkoll Crack Packr

- **Crack Filling Ability** : Strong filling capacity for cracks of up to 3 mm width.
- **Flexibility** : High elongation film that accommodates movement.
- **Mechanical Strength** : Reinforced with glass fiber for superior mechanical strength.
- **Water Proofing** : Water resistant film stops water ingress through cracks.
- **Adhesion** : Very strong adhesion on all absorbent surfaces like plaster, wood, gypsum, POP, asbestos, etc.
- **Usage** : Single pack, Ready-to-use & Easy-to-apply Product.

### Product Features

- **Packaging** : SUNKOLL CRACK PACKR, is supplied in 300 gm., 800 gm., 4 kg. & 20 kg. pack
- **Colours Available** : White
- **Drying Time Touch** : 4 - 8 Hours.

[www.sunkoll.com](http://www.sunkoll.com)

Water Proofing Chemicals | Adhesives | Grouts/Epoxy Grouts | Wall Putty

## How to Apply

- **Cleaning** : Open the cracks and widen the cracks to form a 'V' shaped groove. This will provide a strong base for adhesion of crack packr to the substrate. Clean the area thoroughly to free it from dust and loose particles. It is recommended to use a cutter for opening the cracks.
- **Priming** : Post cleaning apply primer in the opened cracks. For interior & exterior cracks, use **Sunkoll Universal Acrylic Wall Primer**.

APPLICATION	THINNER	DILUTION %	RECOATING PERIOD
<b>STEP 1</b> FIRST COAT SUNKOLL - CRACK PACKR PUTTY KNIFE/ TROWEL	N/A	N/A	N/A
<b>STEP 2</b> SECOND COAT SUNKOLL - CRACK PACKR PUTTY KNIFE/ TROWEL	N/A	N/A	N/A
<b>STEP 3</b> LEVELING	LEVEL THE WALL USING SUNKOLL WALL PUTTY		
<b>STEP 4</b> PRIMER AND TOP COAT	CONTINUE NORMAL PAINTING USING PRIMER & TOPCOAT		

## Additional Information

### Technical Details

- A. Form** : Ready to use paste
- B. Density at 25° C** : 1.28
- C. Drying Time** : Minimum 6 hour depending on temperature & humidity
- D. Flash Point** : Crack Packr is a water based which is not flammable
- E. Consumption** : 75 - 80 running feet / kg / 2 coats (3 mm wide and 5 mm deep)

### Post Painting Care

For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any, at regular intervals of six months.

## Precautions

- Do not apply for cracks of more than 3 mm width.
- Do not apply on wet surfaces.
- Meant for plaster cracks. Do not apply on structural on joint cracks.

## Safety Features

- Kindly refer to the **SUNKOLL CRACK PACKR** gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

## DISCLAIMER

The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee/warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.



### **SUNKOLL Green Building Index :**

SUNKOLL range of products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, SUNKOLL procure the major raw material locally to safeguard environment.

### **SUNKOLL Quality & Safety Assurance**

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.

### **Declaration :**

All the above information and results are provided based on **SUNKOLL** internal quality test. Customer must check before using the product about performance and final expected results. **SUNKOLL** cannot be held responsible for any damage of whatsoever nature at site.

## **SUNKOLL INDUSTRIES LIMITED**

Plot No. 62, Tarang Industrial Estate  
Hadamtda Ta. Kotda Sangani N.H. 8-B  
Rajkot(Gujarat) - 360 311

**TECHNICAL SERVICES & CUSTOMER CARE : +91 70698 82251**

**TOLL FREE : 1800 890 2343**

**Email: [sunkollindltd@gmail.com](mailto:sunkollindltd@gmail.com)**