

SUNKOLL TILE GROUT

TECHNICAL DATA SHEET

SUNKOLL[®]
ABILITY ♦ STABILITY ♦ DURABILITY

नए भारत क नई ताकत

SUNKOLL TILE GROUT is a cement-based grout designed to point tile joints on walls and floors. Produced from carefully selected raw materials for consistency of product, it only requires the addition of water on site.

How To Use



Technical advantage of SUNKOLL TILE GROUT

- Exceptional and consistent quality
- Suitable for areas that will be dry or intermittently wet
- Suitable for joint widths up to 8mm
- Can be used in conjunction with under-tile heating
- Limited flexibility to accommodate some movement
- Available in a range of colours

SUNKOLL TILE GROUT



Use

- For grouting joints between tiles
- Suitable for walls and floors
- Suitable for interior and exterior use
- Suitable for intermittently wet and dry conditions
- Used in kitchens, bathrooms and showers
- **Constraints:** Not suitable if grout is required to be chemically-resistant or completely impermeable.

Mixing

- Allow the mixture to stand for 5 minutes.
- Remix thoroughly before use.
- If SUNKOLL TILE GROUT is used in permanently wet areas, areas where food or cosmetic staining may occur, e.g. kitchens and bathrooms or if increased flexibility is required, the water in the mix should be replaced with SUNKOLL BOND REPAIR -It. Mix as above.
- Note that the grout will dry a shade darker.
- Do not add too much water or attempt to extend the working time by adding more water as this will cause the set grout to be weak with a tendency to crumble.
- It may also cause surface discolouration and variation, especially with darker colours.

SUNKOLL TILE GROUT



नए भारत क नई ताकत

Technical Performances

Joint width	2 to 8mm
Pot life	90 minutes
Final drying time	24 hours at 20°C and 50% humidity
Water demand	1.35 litres per 5kg
Application temperatures	Do not apply in temperatures below 5°C or above 30°C

Important Instructions

- Contains cement, which is alkaline when wet and can cause skin irritation.
- Use eye protection and gloves and avoid prolonged skin contact.
- Avoid inhalation of dust.
- Wash skin contamination away with warm soapy water.
- Remove splashes to the eyes by prolonged irrigation and consult a doctor. Do not ingest.

SUNKOLL TILE GROUT



नए भारत क नई ताकत



SUNKOLL Green Building Index :

SUNKOLL Range of Products are most eco-friendly and suitable to use in all kind of buildings including certified green. Apart from using best of international raw material for best performance, SUNKOLL procure the major raw material locally to safeguard environment.

SUNKOLL Quality & Safety Assurance

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.

Declaration :

Check before using the product about performance and final expected results. **SUNKOLL** cannot be held All the above information and results are provided based on **SUNKOLL** internal quality test. Customer must responsible for any damage of whatsoever nature at site.

UNIT - 1 **SUNKOLL INDUSTRIES LIMITED**

Plot No. 62, Tarang Industrial Estate
Hadamtda Ta. Kotda Sangani N.H. 8-B
Rajkot(Gujarat) - 360 311

UNIT - 2 **SUNKOLL INDUSTRIES LIMITED BARODA**

UNIT - 3 **SUNKOLL INDUSTRIES LIMITED JAIPUR**

UNIT - 4 **SUNKOLL INDUSTRIES LIMITED GUWAHATI**

TECHNICAL SERVICES & CUSTOMER CARE MANAGER : +91 70698 82251

TOLL FREE : 1800 890 2343

Email: sunkollindltd@gmail.com

www.sunkoll.com

Water Proofing Chemicals | Adhesives | Grouts/Epoxy Grouts | Wall Putty